



<p>5DO69750 Island flue Stainless steel and black glass</p> <p>Output, consumption</p> <ul style="list-style-type: none"> • Voltage: 220 – 240 V • Total connected load: 228.4 W • Energy efficiency class: A* • Average power consumption: 49.6 kWh/year • Fan efficiency class: A* • Light efficiency class: A* • Grease filter efficiency class: C* • Noise min./max. Normal level: 48/58 dB* <p>Fan output max. Normal level/Intensive level*: • in extraction mode 550 m³/h / 700 m³/h • in circulation mode 420 m³/h / 560 m³/h * According to EU Regulation No. 65/2014 / Fan capacity according to EN 61591</p> <p>Equipment / comfort</p> <ul style="list-style-type: none"> • Stainless steel and black glass • For ceiling installation above kitchen islands • Optional extraction or circulation mode (carbon filter required for circulation mode) • Electronic control • 4-level fan power (3 power levels + 1 intensive level) controllable through I-Drive and Touch Control with LED display • Intensive levels with automatic reset • Automatic three-level power overrun of 5/10 and 20 minutes • Metal grease filter saturation indicator • Activatable carbon filter saturation indicator • Powerful and quiet blower • Uniform, bright lighting with 4 x 2.1 W LED lamps • Illuminance: 239.4 lux • Colour temperature: 4.000 K • Metal grease filter, dishwasher-safe • Including exhaust air shaft <p>Optional accessories:</p> <ul style="list-style-type: none"> • 5Z 9101X1: Carbon filter <p>Technical data and dimensions</p> <ul style="list-style-type: none"> • Appliance dimensions, extraction: 660 – 1080 x 900 x 600 mm • Appliance dimensions, circulation: 730 – 1150 x 900 x 600 mm • Length of connection cable (cm): 150
--

<p>Optional accessories:</p> <ul style="list-style-type: none"> • 5Z 9101X1: Carbon filter
<p>Available color options:</p>
<p>Accessories:</p>

<p>Features:</p> <ul style="list-style-type: none"> • Device type: island fair • Color of the fireplace: stainless steel • Design: Wandesse • Approval certificates: CE • Length of connection cable (cm): 150 • Height of the fireplace: min. 660 max. 1150 • Height of the unit without chimney (mm): 83 • Net weight (kg): 25 • Control: I-Drive and Touch Control with LED display • Regulation of power levels: 3 + intensive • Max. Fan power exhaust air operation (m³ / h): 550 • Blower power for intensive stage exhaust air operation (m³ / h): 700 • Max. Fan speed recirculation mode (m³ / h): 420 • Blower power at intensive stage circulating air operation (m³ / h): 560 • Number of lamps (pieces): 4 • Sound power (dB (A) re 1 pW): min. 48 Max. 58 • Diameter of exhaust air outlet (mm): 150 • Material of grease filter: aluminum • Odor filter: no As an accessory • Type of air duct: Optional exhaust air or recirculated air • Type of lamps: LED • Total power of the lamps (W): 4x2,1 W • Type of grease filter: aluminum • Filter change reminder: Yes
<p>Consumption and connection values:</p> <ul style="list-style-type: none"> • Connected load (W): 224.2 • Voltage (V): 220/240 • Frequency (Hz): 50/60 • Plug type: Schuko • Length of connection cable (cm): 150 • Type of installation: Inselesse • Net weight (kg): 25 • Position of the fan: motor in the housing

EAN-Nr.:4251003101072

