

New

Effortlessly handleless: Push to open Silent for the InnoTech Atira drawer system



Opens without handles, closes with Silent System

With Push to open Silent, drawers are incredibly easy to open without handles, gently and quietly closing again from just a slight turn of the wrist. Drawers can still be pulled open and guided closed. Instead of springing back, Push to open Silent stores energy and assists the closing cycle as the drawer slowly glides in.

With optional synchronisation, the system can be activated from the edges of large drawer fronts, even with narrow front panel reveals. With optional 10 kg runners, light drawers can be closed just as easily as pot-and-pan drawers up to 50 kg.

Technical details in brief

- ▶ Opening system combined with Silent System
- ▶ Minimal 2.5 mm front panel reveal
- ▶ Drawer energy storage system assists slow closing cycle
- ▶ Drawer can still be guided closed / pulled open
- ▶ Reliable activation from optional synchronisation
- ▶ Clips into place without the need for tools
- ▶ For all nominal drawer lengths and carcass widths of 275 mm and over
- ▶ Units: 10 kg, 20 kg, 30 kg, 50 kg



Design that's hard to resist.
Feel style - with Hettich

Fascinated by solutions.
We call it

Fascin[action]



Further information:
<http://www.hettich.com/short/3e1c7c>

InnoTech Atira double walled drawer system

- ▶ Quadro drawer runner with Push to open Silent, set packaging
- ▶ Full extension runner

Drawer runner



- ▶ Can only be used with Push to open Silent
- ▶ Full extension runner
- ▶ With integrated Silent System
- ▶ Galvanised steel
- ▶ Load capacity to EN 15338, Level 3

Carcase side thickness 16 mm (installed width EB 12.5)

Nominal length mm	Order no. / Load capacity kg			PU
	10 (V6)	30 (V6)	50 (V6+)	
260	9 243 709	9 243 718		1 set
300	9 243 712	9 243 721	9 243 772	1 set
350	9 243 715	9 243 724	9 243 775	1 set
420		9 243 727	9 243 778	1 set
470		9 243 730	9 243 781	1 set
520		9 243 733	9 243 784	1 set
620			9 243 787	1 set

Carcase side thickness 18 mm (installed width EB 10.5)

Nominal length mm	Order no. / Load capacity kg			PU
	10 (V6)	30 (V6)	50 (V6+)	
260	9 243 682	9 243 691		1 set
300	9 243 685	9 243 694	9 243 754	1 set
350	9 243 688	9 243 697	9 243 757	1 set
420		9 243 700	9 243 760	1 set
470		9 243 703	9 243 763	1 set
520		9 243 706	9 243 766	1 set
620			9 243 769	1 set

Carcase side thickness 19 mm (installed width EB 9.5)

Nominal length mm	Order no. / Load capacity kg			PU
	10 (V6)	30 (V6)	50 (V6+)	
260	9 243 655	9 243 664		1 set
300	9 243 658	9 243 667	9 243 736	1 set
350	9 243 661	9 243 670	9 243 739	1 set
420		9 243 673	9 243 742	1 set
470		9 243 676	9 243 745	1 set
520		9 243 679	9 243 748	1 set
620			9 243 751	1 set

Weight ranges for Push to open Silent:

< 10 kg

8 - 20 kg

10 - 30 kg

20 - 50 kg

InnoTech Atira double walled drawer system

- ▶ Quadro drawer runner with Push to open Silent, set packaging
- ▶ Full extension runner

Push to open Silent opening system for InnoTech



Set comprises:

- ▶ 1 Push to open Silent unit, left and right
- ▶ 1 activator, left and right
- ▶ 2 adapters for mounting optional synchronisation

Total weight kg	Quadro kg	Nominal length mm	Order no.	PU
< 10	10 (V6)	260 - 350	9 240 161	1 set
8 - 20	30 (V6)	260 - 520	9 240 162	1 set
10 - 30	30 (V6)	260 - 520	9 240 163	1 set
20 - 50	50 (V6+)	300 - 620	9 240 164	1 set

Recommendation for drawer (front panel height up to approx. 150 mm)*

Nominal length mm	Nominal width mm												
	275	300	350	400	500	600	700	800	900	1000	1100	1200	
260													
300													
350													
420													
470													
520													
620													

Recommendation for pot-and-pan drawer (front panel height up to approx. 300 mm, light to medium duty loading)*

Nominal length mm	Nominal width mm												
	275	300	350	400	500	600	700	800	900	1000	1100	1200	
260													
300													
350													
420													
470													
520													
620													

Recommendation for pot-and-pan drawer, heavy duty (front panel height up to approx. 300 mm, heavy duty loading, e.g. with stacks of plates)*

Nominal length mm	Nominal width mm												
	275	300	350	400	500	600	700	800	900	1000	1100	1200	
260													
300													
350													
420													
470													
520													
620													

Weight ranges for Push to open Silent:

< 10 kg

8 - 20 kg

10 - 30 kg

20 - 50 kg

* Recommendations for applications (front panel 19 mm chipboard, normal household loading), please refer to our online configurator to get more exact recommendations for customer chosen front panel dimensions and materials.

InnoTech Aтира double walled drawer system

- ▶ Quadro drawer runner with Silent System, set packaging
- ▶ Push to open Silent

Optional: synchronisation



- ▶ Recommended for carcase widths of 600 mm and over
- ▶ Synchronisation bar for cutting to length
- ▶ Length 2000 mm
- ▶ Aluminium, anodized
- ▶ Connector for minimising offcut waste
- ▶ plastic, grey

Article	Order no.	PU
1 Synchronisation bar	9 236 718	1/100 each
2 Connector	9 221 295	1/20 each

Installation

